

PRODUCT NUMBER: DG-1200




MATERIAL SAFETY DATA SHEET

Per 29 CFR 1910.1200

DeltaGreen Products, Inc.

13714 Alma Ave., Gardena, CA 90249 Tel: 310-329-1883 Fax: 310-532-0372 E-mail: info@deltagreenonline.com



SECTION I.

EMERGENCY PHONE NUMBER: (310) 532-0353
DATE PREPARED: September 21, 2011

SECTION II. HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

IDENTITY (As Used on Label and List): Ultra Glaze

| CAS Registry No. | %W | %V | Chemical Name | Listed as Carcinogen in NTR, IARC or |
|------------------|----|----|----------------------------------|---|
| | | | | OSHA 1910(z) |
| 111-77-3 | > | 5 | Diethyleneglycol Monmethyl Ether | None |
| 78-51-3 | < | 2 | Tributoxyethl Phosphate | None |
| 38714-47-5 | < | 1 | Zinc Ammonium Carbonate | None |
| 84-74-2 | < | 1 | Dibutyl Phthalate | None |
| | | | | |

SECTION III. PHYSICAL DATA

BOILING POINT: 212 F SPECIFIC GRAVITY 1.01 VAPOR PRESSURE PERCENT VOLOTILE BY VOLUME N/A 64 PERCENT SOLIID BY VOLUME 20 VAPOR DENSITY (AIR=1): >1 SOLUBILITY IN WATER: 100% **EVAPORATION RATE** >1

pH 8-9

APPEARANCE & ODOR: White milky emulsion

SECTION IV. FIRE & EXPLOSION HAZARD DATA

FLASH POINT: None

FLAMABLE LIMITS: LEL None, UEL None

EXTINGUISHING MEDIA: Foam or carbon dioxide or dry chemical

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus with a full facepiece operated in

pressure-demand or other positive pressure mode when fighting fires

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION V. REACTIVITY DATA

STABILITY: Stable. Avoid strong oxidizing agents.

ONDITIONS TO AVOID: Incompatible with strong oxidizing materials.

Page 1 of 2

Product Name: Ultra Glaze Non-Slip Floor Finish

PRODUCT NUMBER: DG-1200

SECTION VI. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Contain and place in suitable container for disposal. Do not discharge to sewer.

WASTE DISPOSAL METHOD: In accordance with local and Federal laws.

CERCLA REPORATBLE QUANTITY Not required

RCRA HAZARDOUS WASTE NO Not a hazardous waste

VOLATILE ORGANIC COMPOUND (VOC) Less then 0.1

SECTION VII. HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

SKIN: Repeated contact can cause moderate irritation, defatting, dermatitis.

EYES: Can cause mild to moderate irritation.

INHALATION: In excess can cause nasal and respiratory irritation.

EMERGENCY AND FIRST AID PROCEDURES:

INGESTION: Induce vomiting, drink plenty of water.

SKIN: Wash with warm water.

EYES: Rinse thoroughly for at least 10 minutes.

SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPITARORY: If TLV of any component is exceeded, wear NIOSH approved gear.

VENTILATION:

LOCAL EXHAUST: To maintain below TLV's

MECHANICAL:

SPECIAL:

PROTECTIVE GLOVES:

Rubber

Sefety glasse

EYE PROTECTION: Safety glasses OTHER PROTECTIVE EQUIPMENT: Not required.

SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLIN G AND STORAGE:

Normal care should be taken to minimize risk of damage. Store in cool dry place.

OTHER PRECAUTIONS:

No other precautions are required.